

OPzS

50PzS250

OPzS Series

NARADA OPzS Series Lead Acid batteries are designed with a combination of die-casting Tubular positive framework and superfluous electrolyte technologies to offer a very high lever of reliability and a long service life. OPzS batteries used special filter and proof design to ensure no acid fog runs over and burning proof, and also convenient examine and maintenance.


The specification of Narada OPzS series batteries make if idea for a wide range of applications such as Telecommunications, Photovoltaic System, Security System, emergency lighting and UPS.

Features & Benefits

- Low maintenance.
- Super long service life.
- Transparent containers, convenient to observe.
- Special filter installation for acid fog proof.
- High quality and high reliability.
- Special pole sealed technology.
- DIN40736-1 compliant.


Construction

- ComponentRaw material
- PositiveLead dioxide
- NegativeLead
- ContainerSAN
- CoverABS
- TerminalCopper
- SeparatorRubber-PVC
- ElectrolyteSulfuric acid







Terminal Dimensions

Cell Dimensions



| | | | | |
|----------------------------------|--|-------------------|-----------------------------------|-----------------|
| Battery Model | 50PzS250 | | | |
| Designed Floating Life | 20 Years | | | |
| Capacity(25°C) | 24HR(11.3A,1.80V) | 10HR(25.0A,1.80V) | 5HR(42.0A,1.80V) | 1HR(134A,1.75V) |
| | 271AH | 250AH | 210AH | 134AH |
| Dimensions | Length | Width | Height | Total Height |
| | 124mm(4.88inch) | 206mm(8.11inch) | 355mm(13.9inch) | 410mm(16.1inch) |
| Approx. Weight | without electrolyte:15.1Kg (33.3 lbs) | | with electrolyte:20.5Kg(45.2 lbs) | |
| Internal Resistance | Full charged at 20°C: 0.0008 Ohm | | | |
| Self Discharge | 3% of capacity declined per month at (20°C) | | | |
| Capacity Affected by Temp.(10HR) | 40°C | 25°C | 0°C | -15°C |
| | 102% | 100% | 85% | 65% |
| Charge Voltage(25°C) | Cycle use | | Float use | |
| | 2.35-2.40V/cell(-5mV/cell/°C), max. Current: 62A | | 2.23V/cell(-3.0mV/cell/°C) | |



Constant Current Discharge Data Units: Amperes (25°C, 77°F)

| End voltage | minutes | hours | | | | | | | | | |
|-------------|---------|-------|------|------|------|------|------|------|------|------|-----|
| | 30 | 1 | 2 | 3 | 4 | 5 | 6 | 8 | 10 | 24 | 48 |
| 1.60V | 212.4 | 145.4 | 90.6 | 65.8 | 52.4 | 44.9 | 39.8 | 32.2 | 26.5 | 11.9 | 6.6 |
| 1.65V | 205.0 | 142.1 | 88.7 | 64.4 | 51.4 | 44.5 | 39.2 | 32.0 | 26.4 | 11.9 | 6.6 |
| 1.70V | 196.8 | 137.7 | 86.8 | 63.3 | 50.9 | 43.9 | 38.6 | 31.6 | 26.2 | 11.8 | 6.5 |
| 1.75V | 189.6 | 133.8 | 84.2 | 61.9 | 50.0 | 43.1 | 37.9 | 30.9 | 25.9 | 11.5 | 6.4 |
| 1.80V | 173.6 | 127.6 | 81.4 | 60.9 | 49.0 | 42.0 | 36.9 | 30.2 | 25.1 | 11.3 | 6.3 |
| 1.85V | 145.9 | 118.4 | 77.0 | 58.5 | 47.5 | 40.8 | 35.6 | 29.4 | 24.8 | 11.0 | 6.0 |
| 19.5V | 124.6 | 94.5 | 67.3 | 52.7 | 44.1 | 37.9 | 32.9 | 26.6 | 22.3 | 10.0 | 5.6 |

Constant Power Discharge Data Units: Watts per cell (25°C, 77°F)

| End voltage | minutes | hours | | | | | | | | | |
|-------------|---------|-------|-------|-------|-------|------|------|------|------|------|------|
| | 30 | 1 | 2 | 3 | 4 | 5 | 6 | 8 | 10 | 12 | 24 |
| 1.60V | 429.7 | 329.2 | 181.6 | 137.8 | 110.0 | 93.1 | 81.9 | 67.5 | 57.0 | 49.1 | 25.2 |
| 1.65V | 407.3 | 305.9 | 180.6 | 136.8 | 109.4 | 92.5 | 81.3 | 67.1 | 56.6 | 48.8 | 25.0 |
| 1.70V | 388.5 | 287.0 | 178.0 | 135.3 | 108.0 | 91.1 | 80.1 | 66.1 | 55.8 | 48.2 | 24.7 |
| 1.75V | 372.7 | 269.8 | 173.1 | 131.8 | 103.9 | 87.9 | 78.4 | 65.1 | 54.8 | 47.5 | 24.4 |
| 1.80V | 357.8 | 254.9 | 166.7 | 128.3 | 101.5 | 83.9 | 74.9 | 62.0 | 52.0 | 44.5 | 23.9 |
| 1.85V | 344.0 | 236.6 | 160.7 | 121.9 | 96.5 | 81.7 | 72.0 | 60.3 | 49.8 | 42.7 | 23.3 |
| 1.95V | 314.3 | 210.9 | 145.8 | 117.9 | 101.5 | 84.6 | 68.6 | 57.3 | 45.2 | 39.1 | 22.3 |

NARADA POWER SOURCE CO.,LTD.
9F, Building A, No. 50 Zijinghua Road, Hangzhou, China
Tel: +86-571-28827013 Fax: +86-571-28828290
Website: www.naradabattery.com E-mail: intl@narada.biz

NARADA ASIA PACIFIC PTE.LTD.
65 Ubi Crescent #07-05 HOLA centre, Singapore
Tel: +65-6848 1191 Fax: +65-6749 3498
E-mail: sales@narada.com.sg

NARADA EUROPE (UK) LIMITED
Spectrum House, Dunstable Road, Redbourn,
St. Albans, Herts AL3 7PR
Tel: +44 (0)845 371 7095 Fax: +44 (0)845 612 2031
E-mail: sales@naradaeurope.com

